

# SULLAIR SCREW COMPRESSOR



Always air, Always there



(Sullair Authorized Distributor in Bangladesh)







## OIL FLOODED SCREW AIR COMPRESSOR

Sullair offers an unmatched full range of oil flooded screw air compressors which are designed for the requirement of almost all manufacturing industries. To meet the demanding Bangladeshi conditions, Global Cynax as an authorized business channel partner & distributor of SULLAIR is offering best screw compressors in Bangladesh from Sullair's different plant locations like USA, China, Japan











## OIL FREE SCREW AIR COMPRESSOR

If you need Class Zero Certified Oil Free Compressed Air Solution, Sullair & Global Cynas are there. Sullair oil free range is available from small capacity to large size & pressure from 15 psi to 725 psi to meet client's specific application needs. Sullair legacy of oil free air compressors has been built on its history of world class compressors specially for pharmaceutical & life science industries.

Though Sullair is an American company, it is backed by Japanese company Hitachi Engineering & Supplied from Japan.

## STATIONERY OIL FLOODED COMPRESSOR



### **AS SERIES**

### Single stage rotary screw air compressor

Power: 4-110 kW Pressure: 7-12 Bar

Capacity: 0.4-20.1 m<sup>3</sup>/min



### **WS SERIES**

### Single stage rotary screw air compressor

Power: 18-75 kW Pressure: 7-12 Bar

Capacity: 2.2-13.5 m<sup>3</sup>/min



## LS SERIES

### Single stage rotary screw air compressor

Power: 90-450 kW Pressure: 7.5-13 Bar

Capacity: 12.6-80.1 m<sup>3</sup>/min



## **LH SERIES**

### Single stage / High efficiency rotary screw air compressor

Power: 22-160 kW
Pressure: 7.6-12 Bar
Capacity: 3.3-32.5 m³/min





## STATIONERY OIL FREE COMPRESSOR



## **DS SERIES**

### Rotary screw oil free air compressor

Power: 75-280 kW

Pressure: 7.5-10.5 Bar

Capacity: 11.1-50.5 m³/min



### **DSP SERIES**

### Rotary screw oil free air compressor

Power: 22-240 kW
Pressure: 7.8-10 Bar
Capacity: 3.7-36.5 m³/min



## **VT/SRL SERIES**

### Scroll oil free air compressor

Power: 1.5-33 kW
Pressure: 8.2-10 Bar
Capacity: 0.16-3.6 m³/min



## **GS SERIES**

### Water flooded oil free air compressor

Power: 15-75 kW Pressure: 6.9-10 Bar

Capacity: 1.84-12.35 m<sup>3</sup>/min

## STATIONERY OIL FLOODED COMPRESSOR / VACUUM SYSTEM



### **TS SERIES**

### Two stage / Energy saving rotary screw air compressor

Power: 75-450 kW
Pressure: 5.5-13 Bar
Capacity: 12-88.6 m³/min



### TH SERIES

### Two stage / High efficiency rotary screw air compressor

Power: 200-250 kW
Pressure: 5.5-13 Bar
Capacity: 31.5-50.1 m³/min



## VS12-VS32 SERIES

### Screw vacuum pump

Power: 11-150 kW Max Vacuum: 29.9 HgV

Capacity: 7.2-100.2 m<sup>3</sup>/min



## VS900-VS6500 SERIES

### VSD screw vacuum pump

Power: 11-110 kW Max Vacuum: 29.9 HgV

Capacity: 14.8-108.5 m<sup>3</sup>/min

3



## PORTABLE COMPRESSOR











| Portable Diesel Engine Driven |                    |                       |              |
|-------------------------------|--------------------|-----------------------|--------------|
| Туре                          | Pressure<br>( bar) | Capacity<br>( m³/min) | Model        |
| Standard                      | 7                  | 5.2                   | 185 (Tier 3) |
|                               | 7-10.3             | 10.6                  | 375          |
|                               | 7-10.3             | 12                    | 425          |
| Mid Range                     | 12.0               | 12.0                  | 425HH        |
|                               | 13.8               | 17                    | 600XH        |
|                               | 10.3               | 21.2                  | 750H         |
|                               | 12.0               | 21.2                  | 750HH        |
|                               | 13.8               | 21.2                  | 750XH        |
|                               | 10.3               | 25.5                  | 900H         |
|                               | 17                 | 15.5                  | 550RH        |
|                               | 20.7               | 24.1                  | 850RH        |
|                               | 24.1               | 25.5                  | 900XH        |
| High<br>Pressure<br>Range     | 24.1               | 31.1                  | 1100XH       |
|                               | 24.1               | 36.8                  | 1300XH       |
|                               | 24.1               | 43.2                  | 1525XH       |
|                               | 34.5               | 30.3                  | 1070XHH      |
|                               | 34.5               | 35.4                  | 1250XHH      |

## RELIABILITY DURABILITY PERFORMANCE





| Portable Electric Driven |                   |                     |  |  |
|--------------------------|-------------------|---------------------|--|--|
| Pressure (bar)           | Capacity (m³/min) | Model               |  |  |
| 12                       | 21.2              | E750HH              |  |  |
| 13.8                     | 21.2              | E750XH              |  |  |
| 10.3                     | 25                | E900H               |  |  |
| 8                        | 27.2              | E1000               |  |  |
| Portable Oil Free        |                   |                     |  |  |
| Pressure (bar)           | Capacity (m³/min) | Model               |  |  |
| 8.6                      | 43.9              | OFD1550<br>(Tier 4) |  |  |

## **LUBRICATION**



www.globalcynax.com

### **SULLAIR ASIA PTE LTD**

Add: 30 Pioneer Crescent, #10-15,

West Park BizCentral, Singapore 628560

Tel: +65 6305 7442 SEA.enquiry@sullair.com





## DOWNSTREAM TREATMENT SYSTEM & PARTS



## HIGH EFFICIENCY COMPRESSED AIR FILTERS

### **MP Series**

Flow Capacity: 1-40 m<sup>3</sup>/min

Max. Working Pressure:

16 bar

Filtration Grade:

1 μm / 0.01 μm / Oil Vapor Removal

Accessories:

Automatic Drain & DP Indicator

### **SP Series**

Flow Capacity:

1-195 m<sup>3</sup>/min

Max. Working Pressure:

10 bar

Filtration Grade:

 $1 \mu m / 0.01 \mu m / Oil Vapor Removal$ 



## REFRIGERATION AIR DRYER

### **SRC Series**

Flow Capacity:  $0.5-110 \text{ m}^3/\text{min}$ Max. Working Pressure: 12 / 14 / 16 barDewpoint: +3-8 DegC



# REGENERATIVE DESICCANT AIR DRYER

### **SPR Series**

Type: Heatless
Flow Capacity: 3.6-96 m³/min
Dewpoint: -40 DegC

## G C GLOBAL CYNAX

## **ABOUT US**

### Who We Are?

Global Cynax Bangladesh, an authorized business channel partner of Sullair for Bangladesh, is offering Sullair compressed air solutions & services throughout Bangladesh. Since 1965, Sullair is an industry-leader in compressed air solutions. Global Cynax is proud to offer these American air compressors to meet the needs of clients throughout Bangladesh. For any kind of industries like textile, garments, cement, steel, paper, plastic, chemical, food & beverage, feed mill & grain processing, pharmaceutical, ceramics, power plant, oil & gas etc., our professional team can match you with the products that's right for your exact air needs.

### Why choose Global Cynax for your compressor?

Since 2007, we have been working with the best global manufacturers, which means if you choose us, you always have access to the best air compressor products & services on the market. And more than one and half decade of experience merges with modern technologies to exceed our clients expectations, you can rely & trust us to help you choose the right solutions & products for your needs.



## **GET IN TOUCH**

## G C GLOBAL CYNAX

### **DHAKA OFFICE**

Suite # A-5, 5th floor, Ring Tower, 32-35 Ring Road, Adabor, Dhaka 1207

### CHATTOGRAM OFFICE

Kader Tower (5th Floor), 128 Jubilee Road, Chittagong.

### **FACILITY UNIT**

Kalampur, Opposite to Buildtrade, Dhamrai, Dhaka 1350

### **MOBILE**

+8801999447777, +8801999337777

### EMAIL

gc@globalcynax.com

### WEBSITE

www.globalcynax.com